

IIP Docket No. 200315232-1

**RECEIVED
CENTRAL FAX CENTER****AUG 16 2007****AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Canceled)
2. (Previously presented) The optical disk drive of claim 21, wherein the encoder is additionally configured to track the disk angular orientation features, the disk angular orientation features molded within the region distinct from the label region.
3. (Previously presented) The optical disk drive of claim 21, wherein the OPU is additionally configured to track the disk angular orientation features, the disk angular orientation features defined within the label region.
4. (Currently amended) The optical disk drive of claim 21, additionally comprising a control procedure to coordinate disk speed data from the encoder with the OPU during application of the image.
5. (Canceled)
6. (Previously presented) A processor-readable medium as recited in claim 22, wherein the instructions for tracking track the disk angular orientation features with the OPU.
7. (Previously presented) A processor-readable medium as recited in claim 22, wherein the instructions for tracking track the disk angular orientation features with the encoder.

HP Docket No. 200315232-1

8. (Currently amended) A processor-readable medium as recited in claim 522, wherein the controlling comprises instructions for:

processing the disk speed data to determine times when the speed of the spindle motor should be increased and times when the speed of the spindle motor should be decreased to maintain desired speed.

9. (Currently amended) A processor-readable medium as recited in claim 522, wherein the interpreting comprises instructions for:

distinguishing between a first and a second signal received from the encoder, wherein the first and second signals result from differences in light reflection corresponding to the presence or absence of the disk speed features.

10. (Currently amended) A processor-readable medium as recited in claim 522, wherein the interpreting comprises instructions for:

distinguishing between a first and a second signal received from the encoder, wherein the first signal results when light is reflected off a mirrored surface to a sensor and the second signal results when light is reflected by a saw tooth feature that also deflects a portion of the light away from the sensor.

11. (Currently amended) A processor-readable medium as recited in claim 522, wherein the interpreting comprises instructions for:

distinguishing between a first and a second signal received from the encoder, wherein the first signal results when light is reflected off a mirrored surface and wherein the second signal results when light is reflected by a substantially circular molded pit that also deflects a portion of the light away from the sensor.

12. (Currently amended) A processor-readable medium as recited in claim 522, wherein

HP Docket No. 200315232-1

the interpreting comprises instructions for:

distinguishing between the output signals, wherein the output signals are associated with levels of light reflectivity within a region defined on a mirror surface adjacent to the coating on the label side of the disk.

13. (Currently amended) An optical disk drive, comprising:

means for controlling a rate at which a spindle motor spins an optical disk;

means for gathering disk speed data by tracking a plurality of substantially identical disk speed features defined on the optical disk as the optical disk is spun by the spindle motor, each of the disk speed features spaced apart substantially equally in a first annular ring at a first radial position on the optical disk and having an angular span that is substantially identical to an angular span of a gap between each two of the disk speed features;

means for tracking, with an OPU, disk angular orientation data defined by disk angular orientation features defined in a second annular ring at a second radial position on the optical disk, wherein the second annular ring abuts the first annular ring; and

means for labeling the optical disk according to the disk speed data and the disk angular orientation data.

14. (Currently amended) The optical disk drive of claim 13, additionally comprising:

~~means for tracking, with an OPU, disk angular orientation data defined by disk angular orientation features; and~~

means for passing the disk angular orientation data to the means for labeling to create an image having a desired angular orientation on a coating on the optical disk.

15. (Currently amended) The optical disk drive of claim 13, ~~additionally comprising:~~

~~means for tracking, with an encoder, wherein the disk angular orientation features are molded disk angular orientation features located radially inside an area on the optical disk~~

HP Docket No. 200315232-1

reachable by an OPU, to produce the disk angular orientation data; and
~~means for using the disk angular orientation data when marking a coating on the optical disk.~~

16. (Original) The optical disk drive of claim 13, additionally comprising:
means for processing the disk speed data from an encoder to determine times when speed of the spindle motor should be increased and times when the speed of the spindle motor should be decreased.

17. (Previously presented) The optical disk drive of claim 13, wherein the means for gathering disk speed data comprises:
means for distinguishing between a first and a second signal received from an encoder, wherein the first and second signals result from differences in light reflection corresponding to the presence or absence of the disk speed features.

18. (Currently amended) The optical disk drive of claim 13, wherein the means for gathering disk speed data comprises:
means for distinguishing between a first and a second signal received from an encoder, wherein the first signal results when light is reflected off a mirrored surface to a sensor and the second signal results when light is reflected to the sensor by a saw tooth feature that also deflects a portion of the light away from the sensor.

19. (Currently amended) The optical disk drive of claim 13, wherein the means for gathering disk speed data comprises:
means for distinguishing between a first and a second signal received from an encoder, wherein the first signal results when light is reflected off a mirrored surface to a sensor and wherein the second signal results when light is reflected to the sensor by a substantially circular

HP Docket No. 200315232-1

molded pit that also deflects a portion of the light away from the sensor.

20. (Original) The optical disk drive of claim 13, wherein the means for gathering disk speed data comprises:

means for distinguishing between encoder sensor outputs associated with levels of light reflectivity within a region defined on a mirror surface adjacent to a coating on the disk.

21. (Currently amended) An optical disk drive, comprising:

a spindle motor to turn an optical disk;

an OPU to apply an image to a coating within a label region of the optical disk; and

an encoder configured to track substantially identical disk speed features in a first annular ring at a first radial position on the optical disk in a region distinct from the label region so as to thereby obtain disk speed data, the disk drive further configured to track disk angular orientation features different from the disk speed features in a second annular ring at a second radial position on the optical disk so as to thereby obtain angular orientation data, the second annular ring abutting the first annular ring, the disk angular orientation features different from the disk speed features, and at least some of the disk angular orientation features having the same an overlapping angular position as with at least some of the disk speed features.

22. (Currently amended) A processor-readable medium comprising processor-executable instructions for labeling an optical disk, the processor-executable instructions comprising instructions for:

controlling a spindle motor within an optical disk drive to regulate angular speed of the optical disk;

interpreting output signals of an encoder resulting from sensation of substantially identical disk speed features defined in a first annular ring at a first radial position on the optical disk as the optical disk is spun by the spindle motor to produce disk speed data;

HP Docket No. 200315232-1

tracking disk angular orientation features defined in a second annular ring at a second radial position on the optical disk and different from the disk speed features to produce disk angular orientation data, at least some of the disk angular orientation features having the same an overlapping angular position as with at least some of the disk speed features, and the second annular ring abutting the first annular ring; and

marking a coating on the optical disk with an OPU, wherein the OPU is operated according to the disk speed data and the disk angular orientation data.

23. (Canceled)